


iBRID™ MX6

Multi-Gas Monitor

■ The World's First Gas Monitor with a Full-Color Display



Get ready to see hazardous levels of oxygen, toxic and combustible gas, and volatile organic compounds (VOCs) like never before. The MX6 iBRID™ is more than an intelligent hybrid of Industrial Scientific's best monitoring technologies. It's the first gas monitor to feature a full-color LCD display screen.

The display improves safety with clear readings in low-light, bright-light or anywhere in between. Whether the work is outside, inside or underground, it's easy to see what gas hazards lurk in the

immediate work environment.

And a color display is more than eye-catching. It allows the user to step through instrument settings and functions with an intuitive menu and the instrument's five-way navigation button. It even supports the option of on-board graphing for easily interpreted direct readings and recorded data.

Plus, the MX6 iBRID is our most rugged instrument ever. It carries a lifetime warranty and is fully compatible with our DS2 Docking Station™ and iNet™ Instrument Network.

**INDUSTRIAL
SCIENTIFIC**

www.indsci.com




THE MX6 iBRID™ COLOR DISPLAY

Enhanced Visibility – Expanded Functionality



The MX6 clearly shows real-time readings in PPM or % by volume.



An intuitive menu provides easy access to features and setup.



Datalog trends and direct readings can be viewed graphically.



Calibration progress and results are shown for each sensor.



A "calibration due" warning appears for each relevant sensor.



Bright red numerals and a flashing backlight show alarm conditions.



Alarms shown with "Go/No Go" text and flashing backlight.



Color-coded text shows test or calibration results at a glance.

ACCESSORIES



- Stand-alone operation
- Link up to 100 IDS modules – dock thousands of instruments
- Automatic instrument calibration, record keeping, diagnostics and recharging
- Utilizes one central database
- Multilingual display
- iNet™ compatible

CHARGER / DATALINK



- Instantly download event logs and datalog data while instrument battery charges
- Quickly and easily configure instrument settings
- Also available – datalink only



- The aspirated version can remotely draw samples from a distance of 30.5 meters (100 feet).

ORDERING INFORMATION

MX6 iBrid™ Part Number – MX6-ABCDEFGHIJ			
A-E (Common Configurations)	F	G	H
K1230 – LEL, CO, H ₂ S, O ₂	1 – Li-ion	0 – Diffusion	0 – English (No Manual)
K0230 – LEL, H ₂ S, O ₂	2 – Li-ion/Ext. Range	1 – Pump	1 – English
K1030 – LEL, CO, O ₂	3 – Alkaline		2 – French
K0030 – LEL, O ₂	4 – Li-ion MSHA/AUS		3 – Spanish
K123R – LEL, CO, H ₂ S, O ₂ , PID	5 – Li-ion/Ext. Range		4 – German
K1235 – LEL, CO, H ₂ S, O ₂ , SO ₂	MSHA/AUS		5 – Italian
K0235 – LEL, H ₂ S, O ₂ , SO ₂	6 – Alkaline MSHA/AUS		6 – Dutch
A-E (Common Industry Configurations)			7 – Bahasa
KJ53R – LEL, CO/H ₂ S, O ₂ , SO ₂ , PID Petroleum Refining			8 – Portugese
K103Q – LEL, CO, O ₂ , CO ₂ Brewing/Bottling/Wineries			
KJ538 – LEL, CO/H ₂ S, O ₂ , SO ₂ , ClO ₂ Pulp/Paper			
K673R – LEL, O ₂ , NH ₃ , Cl ₂ , PID HazMat			
M1030 – CH ₄ (%), CO, O ₂ Mining			
M143D – CH ₄ , CO, O ₂ , NO ₂ , NO Mining (Diesel Applications)			

Build and price your MX6 online with the MX6 instrument builder.

www.indsci.com/MX6builder.asp

ACCESSORY ORDERING INFORMATION

PART #	DESCRIPTION	PART #	DESCRIPTION
MX6KIT-K1230211	Confined Space Kit, 4-gas w/Pump	18107243	MX6 Truck mount charger
MX6KIT-K123R211	Confined Space Kit, 4-gas/PID w/Pump	18107250	MX6 Truck mount charger, hard-wired
18106765	SP6 Motorized Sampling Pump Module	17131038-1	Li-ion Battery Pack, UL/CSA/ATEX
18107078	Hand Aspirated Pump	17131038-2	Li-ion Ext. Battery Pack, UL/CSA/ATEX
18106724-ABC+	DS2 Docking Station™ for MX6	17131038-4	Li-ion Battery Pack, MSHA/AUS
18107086	Datalink Assembly	17131038-5	Li-ion Ext. Battery Pack, MSHA/AUS
18107094	Battery Charger/Datalink, universal	17131046-3	Alkaline Battery Pack, UL/CSA/ATEX
18107011	Battery Charger, 12V	18101046-6	Alkaline Battery Pack, MSHA/AUS
18107136	Battery Charger, 5-Unit	18106856	Hard Leather Carrying Case, Diffusion
		18106880	Hard Leather Carrying Case, Aspirated

+ Ordering Information

A = Wireless Compact Flash (0 – none, 1 – installed +\$125.00)

B = number of iGas Readers at \$45.00 each

C = Power Cord (0 – US, 1 – UK, 2 – EU, 3 – AUS, 4 – ITA, 5 – DEN, 6 – SWZ)

Supplied with Monitor:

universal charger, nylon carrying case, belt clip, calibration cup, wrist strap, maintenance tool, manual, quick start guide, training CD, calibration tubing, dust filter/water stop (aspirated), calibration fitting (aspirated), sample tubing (aspirated).





Case Material:

Lexan/ABS/Stainless Steel w/protective rubber overmold

Dimensions:

135 mm x 77 mm x 43 mm (5.3" x 3.05" x 1.7") – diffusion version

Weight:

409 g (14.4 oz) typical

Display/Readout:

STN Color Graphic LCD

Sensors:

Combustible gas/Methane – Catalytic Diffusion/Infrared
 Oxygen and Toxic gases – Electrochemical
 CO₂ – Infrared
 VOCs – Photolonization

Measuring Ranges:

Combustible Gases – 0 to 100% LEL in 1% increments
 Methane – 0 to 5% of volume in 0.1% increments
 (0 to 100% vol. optional)
 Oxygen – 0 to 30% of volume in 0.1% increments
 Carbon Monoxide – 0 to 999 ppm in 1 ppm increments
 (0 to 9,999 ppm optional)
 Hydrogen Sulfide – 0 to 500 ppm in 0.1 ppm increments
 Hydrogen, Nitric Oxide – 0 to 999 ppm in 1 ppm increments
 Chlorine – 0 to 99.9 ppm in 0.1 ppm increments
 Nitrogen Dioxide, Sulfur Dioxide – 0 to 99.9 ppm in 0.1 ppm increments
 Hydrogen Cyanide, Hydrogen Chloride – 0 to 30 ppm in 0.1 ppm increments
 Ammonia – 0 to 200 ppm in 1 ppm increments
 Chlorine Dioxide – 0 to 1 ppm in 0.01 ppm increments
 Phosphine – 0 to 5 ppm in 0.01 ppm increments
 (0 to 999 ppm optional)
 Ethylene Oxide – 0 to 10 ppm in 0.1 ppm increments
 Carbon Dioxide – 0 to 5% of volume in 0.1% increments
 VOCs (general) – 0 to 2,000 ppm in 0.1 increments

Operating Temperature Range:

-20°C to 55°C (-4°F to 131°F) typical

Operating Humidity Range:

15% to 95% non-condensing (continuous) typical

Power Source/Run Times:

Rechargeable Lithium-ion (Li-ion) Battery Pack (24 hours typical)
 Rechargeable, Extended-Range Lithium-ion (Li-ion) Battery Pack
 (36 hours typical)
 Replaceable AA Alkaline Battery Pack (10.5 hours typical)

Certifications:

IECEX/ATEX: Intrinsic Safety: EEx ia d IIC T4
 Equipment Group and Category: II 2G
 UL: Class I, Groups A,B,C,D T4; AEx ia d IIC T4
 CSA: Class I, Groups A,B,C,D T4 (pending)
 MSHA: CFR30, Part 18 and 22,
 Intrinsically safe for methane/air mixtures (pending)

REV 0507

INDUSTRIAL SCIENTIFIC CORPORATION

CORPORATE HEADQUARTERS

1001 Oakdale Road • Oakdale, PA • 15071-1500 • USA

www.indsci.com



AMERICAS

Tel.: +1-412-788-4353
 Fax: +1-412-788-8353
 info@indsci.com

ASIA PACIFIC

Tel.: 86-10-8497-3970
 Fax: 86-10-8497-3971
 sales@isc-cn.com

EUROPE

Tel.: 33-3-21-60-80-80
 Fax: 33-3-21-60-80-00
 info@groupoldham.com

AUSTRALIA / NZ

Tel.: +61-2-8870-3400

GERMANY

Tel.: +49-231 / 9241-0

MIDDLE EAST

Tel.: +971-50-455-8518

SINGAPORE

Tel.: +65-6561-7377

UNITED KINGDOM

Tel.: +44-0-1280-706114

CZECH REPUBLIC

Tel.: +420-234-622-222/3

ITALY

Tel.: +39-011-3801371

NETHERLANDS

Tel.: +31-76-5427-609

SWITZERLAND

Tel.: +41-26-652-51-18